### **ITEM 010460**

Item 0104601 - HANDLING COLD RECLAIMED ASPHALT PAVEMENT - 0-6"
Item 0104602 - HANDLING COLD RECLAIMED ASPHALT PAVEMENT - 7"
Item 0104603 - HANDLING COLD RECLAIMED ASPHALT PAVEMENT - 8"
Item 0104604 - HANDLING COLD RECLAIMED ASPHALT PAVEMENT - 9"
Item 0104605 - HANDLING COLD RECLAIMED ASPHALT PAVEMENT - 10"
Item 0104606 - HANDLING COLD RECLAIMED ASPHALT PAVEMENT - 11"
Item 0104607 - HANDLING COLD RECLAIMED ASPHALT PAVEMENT - 12"
Item 0104608 - HANDLING COLD RECLAIMED ASPHALT PAVEMENT - 13"
Item 0104609 - HANDLING COLD RECLAIMED ASPHALT PAVEMENT - 14"
Item 0104610 - HANDLING COLD RECLAIMED ASPHALT PAVEMENT - 15"

## **DESCRIPTION**

Work under this item shall consist of the movement of the cold reclaimed asphalt pavement sub base material to and from the roadway; spreading the material after the proper sub grade elevation has been achieved; and fine grading of the cold reclaimed asphalt pavement to plan as required. Compaction shall be accomplished under the reclamation item included in the contract.

# **REFERENCED ITEMS**

0103301

#### **REQUIRED SUBMITTALS**

None

#### **MATERIALS**

None

### **CONSTRUCTION METHODS**

The Contractor shall investigate and verify the amount of cold reclaimed asphalt pavement to be moved and where it can be stored (windrow or stockpile) while the subgrade is under excavation. The work associated with excavating, removing, and disposing of any sub base or sub grade materials (non-reclaimed materials) shall be included and paid for under bid item #0103301.

In areas where the proposed grade lines require only minor subgrade changes, the reclaimed material may be placed in windrows or stockpiled while the additional excavation is performed. The Engineer must approve of any plan to windrow the cold reclaimed asphalt pavement. The area of stockpile may be determined by the

1 010460

Contractor but must be approved by the Engineer. The Contractor may not interfere with commercial storefronts or residential access, and as such, must maintain a safe and clear opening free of any obstructions to all driveways and roads.

Any areas affected by the temporary stockpiling or windrowing of cold reclaimed asphalt pavement shall be reestablished or repaired as directed by the Engineer at no cost.

The Contractor shall be responsible for the scheduling of work under this item so as not to interfere with any sequence of operations developed for this project. Delays as a result of work required under this item shall not constitute a claim for an extension of contract time.

# METHOD OF MEASUREMENT

This work shall be measured for payment by the actual number of square yards equal to the area of "Handling Cold Reclaimed Asphalt Pavement (Depth)" completed and accepted. This item will be measured for payment only one time, regardless of the actual number of times the material is handled or moved.

# **BASIS OF PAYMENT**

The handling of the cold reclaimed asphalt pavement work shall be paid for at the contract unit price per square yard of "HANDLING COLD RECLAIMED ASPHALT PAVEMENT (DEPTH)" complete and accepted, which price shall include all materials, equipment, tools, disposal of surplus material and labor incidental thereto. The reclamation of the asphalt pavement shall be paid for as a separate item. In addition, the establishment of any and all stockpile areas shall be included in the unit price for this item.

<b>ITEM</b>	<b>DESCRIPTION</b>	<u>UNIT</u>
0104601	Handling Cold Reclaimed Asphalt Pavement - 0-6" Depth	S.Y.
0104602	Handling Cold Reclaimed Asphalt Pavement - 7" Depth	S.Y.
0104603	Handling Cold Reclaimed Asphalt Pavement - 8" Depth	S.Y.
0104604	Handling Cold Reclaimed Asphalt Pavement - 9" Depth	S.Y.
0104605	Handling Cold Reclaimed Asphalt Pavement - 10" Depth	S.Y.
0104606	Handling Cold Reclaimed Asphalt Pavement - 11" Depth	S.Y.
0104607	Handling Cold Reclaimed Asphalt Pavement - 12" Depth	S.Y.
0104608	Handling Cold Reclaimed Asphalt Pavement - 13" Depth	S.Y.
0104609	Handling Cold Reclaimed Asphalt Pavement - 14" Depth	S.Y.
0104610	Handling Cold Reclaimed Asphalt Pavement - 15" Depth	S.Y.

010460